

```
{ Main Program }
{$IDATA}
```

```
begin

  DDRA:= %11001010; //
  EnableInts;

  eLW1:= $05050A0A;
  eLW2:= $02020202;
  eB1:= $55;
  eb2:= $02;
```

```
// LW:= eLW1;
```

```
loop
```

```
  PortA.3:= true;      //Pin7
  PortA.6:= true;      //Pin2   nok !
  PortA.7:= true;      //Pin3
  mdelay(1);
  PortA.3:= false;
  PortA.6:= false;
  PortA.7:= false;
```

Lister - [e:\AVR\CO Projekte\Tiny412_1\Tiny412_1.eep]

Datei Bearbeiten Optionen Codierung Hilfe

```

|:10000000FFFFFFFFFFFFFFFF08202020202052
|:100010002020310820205465737420205555553711
|:0C0020005555553700000000000000009E
|:00000001FF

```

Lister - [e:\AVR\CO Projekte\Tiny412_1\Document.eep]

Datei Bearbeiten Optionen Codierung Hilfe

```

|:100000000A0A05050202020255020820202020CB
|:100010002020310820205465737420205555553711
|:10002000555555370000000000000000FFFFFFFF9E
|:10003000FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFD0
|:10004000FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFC0
|:10005000FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFB0
|:10006000FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFA0
|:10007000FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFF90
|:00000001FF

```